

A better environment inside and out.™

Solar Gard® TrueVue™

For a clear view day or night

Solar Gard® TrueVue™ window film

provides optimum clarity for stunning exterior views day and night.



TrueVue offers you:

- Protection from the sun's damaging ultraviolet rays
- Rejects up to 82% of the total solar energy to increase your comfort
- Reduces both the cost of air conditioning and your carbon footprint
- Controls hot spots and uneven temperature zones
- Reduces glare by up to 94%
- Helps to increase your interior daytime privacy

TrueVue comes in four different shades, 5, 15, 30 and 40:

- Provides you with a choice in visual appearance and solar performance

TrueVue is made by one of the world's leading window film manufacturers in quality and performance.

It comes with a limited lifetime residential or a 10 year commercial warranty.



TrueVue features and benefits:

Low internal and external reflection

- Provides you with superior external views day or night

Solar heat protection

- Decreases energy costs by reducing the need for air conditioning
- Improves comfort
- Reduces hotspots

Warm rich tone

- Significantly reduces glare
- Gives glass a pleasing neutral appearance

Blocks up to 99% of UV

- Protects expensive artwork, precious antiques, retail merchandise, carpets, flooring and furniture from damaging UV rays
- Protects against premature aging and skin cancer

Limited lifetime residential and 10 year commercial warranty

- Guarantees you a minimum length of service



Performance measurements*

	Solar energy transmittance (%)	Total solar energy absorptance (%)	Solar energy reflectance (%)	Visible light transmittance (%)	Visible light reflectance exterior (%)	Visible light reflectance interior (%)	Emissivity	Winter u-factor (Btu hr/ft ² °F)	Shading coefficient	Solar heat gain coefficient	Solar selectivity index - luminous efficacy (MLT/SC)	Light to solar heat gain factor (MLT/SHGC)	Ultraviolet blocked (%) (300 to 380 nanometers)	Total solar energy rejected (%)	Solar heat gain reduction (%)	Glare reduction (%)
TrueVue™ 40	38	40	22	39	14	10	.75	.99	.57	.49	.69	.80	>99	51	43	56
TrueVue™ 30	27	41	32	31	22	13	.75	.99	.45	.39	.70	.81	>99	61	55	65
TrueVue™ 15	9	40	51	12	45	23	.75	.99	.24	.20	.51	.60	>99	80	76	87
TrueVue™ 5	6	43	51	5	45	8	.75	.99	.21	.18	.25	.29	>99	82	79	94

* Performance results were obtained through measurements on the inside of 3mm (1/8") thick clear glass and were then calculated using NFRC methodology and LBNL Window 5.2 software, and are subject to variations within industry standards and only intended for estimating purposes.

